

[54] APPARATUS FOR MANUAL ADJUSTMENT OF A CLOCK

[75] Inventor: **Dieter Hafner**, Nurnberg, Fed. Rep. of Germany

[73] Assignee: **Diehl GmbH & Co.**, Nurnberg, Fed. Rep. of Germany

[21] Appl. No.: **102,250**

[22] Filed: **Dec. 10, 1979**

[30] Foreign Application Priority Data

Dec. 14, 1978 [DE] Fed. Rep. of Germany 2853911

[51] Int. Cl.³ **G04C 9/08; G04G 5/00; G04G 5/02**

[52] U.S. Cl. **368/187; 368/188; 368/294**

[58] Field of Search **58/23 R, 23 D, 85.5, 58/91; 368/187, 188, 294**

[56] References Cited

U.S. PATENT DOCUMENTS

1,410,050 3/1922 Wyss 58/46 W
4,040,248 8/1977 Laesser 58/19 A

FOREIGN PATENT DOCUMENTS

2111209 1/1971 Fed. Rep. of Germany .
2249588 4/1974 Fed. Rep. of Germany .
2658105 6/1976 Fed. Rep. of Germany .
2501973 7/1976 Fed. Rep. of Germany 58/85.5
69989 9/1915 Switzerland .
259511 1/1949 Switzerland .

Primary Examiner—Edith S. Jackmon

Attorney, Agent, or Firm—Burns, Doane, Swecker & Mathis

[57] ABSTRACT

An actuating element for the manual adjustment of a clock comprises a rotating collar face which is arranged around the time indicating device of the clock. In a mechanical or electromechanical clock, the rotating movement of the rotating collar face is transmitted through gearing to the dial train of the clock. In an electronic clock pulse-producing elements are arranged on the collar and pulse-receiving elements are fixed in the clock to produce individual pulses or pulse trains which can be counted in according to the backward counting input of the time storage which is in operative connection with the indicating element of the clock.

9 Claims, 4 Drawing Figures

